



MILTECH™ 9113

Managed Military Grade Embedded Ethernet Switch 12 x 10/100/1000TX Ports + 2 x Gigabit Fiber Ports

The MILTECH 9113 is specifically designed for complex traffic applications featuring IEEE-1588 capabilities suitable for rugged military mobile tactical platforms, which require network-centric interfaces.

With 12 triple-speed (10/100/1000Mbps) ports + 2 Interfaces SGMII the MILTECH 9113 features both L2/L3 network switching and static routing capabilities, including virtual LANS (VLANS), traffic prioritization/ QoS, IPv4/IPv6 support, and bandwidth aggregation. It supports all the latest networking protocols for redundancy, security, multicast, and management.

With the industry's smallest footprint, the MILTECH 9113 measures only 70 x 97mm to offer performance and a combination of size, weight, and power (SWaP) in the industry, saving valuable real estate for devices that make mobile platforms highly effective.

Conformally coated and with board-to-board connectors, it can easily be integrated as a module-based network building block in any military-grade communications platform. The MILTECH 9113 board-level communication solution will withstand working temperatures of -45°C to +85°C and will comply with MIL-STD-810 & MIL-STD-461.



SPECIFICATIONS

ETHERNET PORTS:	<ul style="list-style-type: none">• 12 Gigabit Copper Ethernet integrated PHYs & magnetics.• 2xSGMII interface for direct connection to 2 x 1G Fiber interfaces or carrier PHY device (with dedicated firmware) for additional two copper ports.
-----------------	---



SPECIFICATIONS

<p>NETWORKING:</p>	<ul style="list-style-type: none"> • Energy efficient Ethernet, IEEE 802.3az • Wire-speed hardware-based 14 ports Gigabit Ethernet Switch – L2 & L3 capabilities • L3-Static Routing capabilities. • 1588V2 PTP with two-step clock. • Multicasting (IGMP Snooping), GARP, GMRP, MLD and GVRP up to 8K groups for both IPv4 and IPv6 • Broadcasting and flooding Control up to 8K Groups • 802.1q Tagged based VLAN up to 4K VLAN groups • Bridge Support for VLAN Q-in-Q • Link Aggregation 802.3ad • WEB, CLI, Telnet , SNMP V2/V3 management • QoS Multi-Layer Classifier: 802.1p, EtherType, VLAN-ID, IPv4/6 DSCP/ToS, and UDP/TCP ports & ranges traffic classification • DSCP remarking for both IPv4 and IPv6 frames • Multiple ACLs per port for optimal usage of Content Aware Policers • Storm controllers for flooded broadcast, multicast and unicast • Spanning Tree (802.1d), RSTP (802.1w) and multiple Spanning Tree (802.1S) for fast recovery rings • Up to 4K egress VLAN tag operations
<p>NETWORKING: Quality of Service</p>	<ul style="list-style-type: none"> • QoS Multi-Layer Classifier: 802.1p, EtherType, VLAN-ID, IPv4/6 DSCP/ToS, and UDP/TCP ports & ranges traffic classification. • Per port WFQ and Strict Queuing scheduling • DSCP remarking for both IPv4 and IPv6 frames • Ingress policer and ingress shaper per port with 500Kbps granularity • Egress shaper per port with 500Kbps granularity • Full-duplex flow control (IEEE802.3X) and half-duplex backpressure
<p>NETWORKING: Quality of Service</p>	<ul style="list-style-type: none"> • Security via Radius Authentication 802.1x, Port / MAC access control • Port Security • Per port ingress and egress port mirroring • Mirroring per VLAN • Private VLAN support per VLAN (Isolated and Promiscuous ports) • Advanced ACL through hardware based match patterns • Content Aware Policers for generic MAC, ARP, IPv4, IPv6 protocols • Content Aware Policers actions are permit/deny, police, count • Multiple ACLs per port for optimal usage of Content Aware Policers • Storm controllers for flooded broadcast, multicast and unicast
<p>CONNECTORS:</p>	<ul style="list-style-type: none"> • Module: Samtec P/N: ERM8-075-02.0-S-DV-TR • Mating connector: Samtec P/N: ERF8-075-05.0-S-DV-K-TR
<p>STANDARDS:</p>	<ul style="list-style-type: none"> • MIL-STD-461E MIL-STD-810F GM IP67. When incorporated in a suitable enclosure
<p>PERFORMANCE:</p>	<ul style="list-style-type: none"> • 8K MAC address
<p>POWER:</p>	<ul style="list-style-type: none"> • Model 9113-000 input power: 6VDC to 36VDC, maximal power consumption 9.3W • Model 9113-001 input power: 3.3VDC ±3%, maximal power consumption 8.5W
<p>ELECTROMAGNETIC:</p>	<ul style="list-style-type: none"> • MIL-STD-461E Electromagnetic compatibility • CE-102, CS-114, CS-115, CS-116, RE-102, RS-103. When incorporated in a suitable enclosure



SPECIFICATIONS

PHYSICAL:	<ul style="list-style-type: none"> • Dimensions: 97mm (L) * 70mm (W) * 19.8 (H) / 3.82" (L) * 2.75" (W) * 0.78" (H) • Approx Weight: 90gr • Mounting Holes: 6 x Spacer with Thread, #4-40 NC
MANAGEMENT:	<ul style="list-style-type: none"> • Ethernet Switch console via the carrier interface connector (RS232) • Ethernet Ports Status (Link/Activity) via carrier interface connector serial-bit-stream (optional direct single LED indications for 12 copper ports)
OPERATING TEMPERATURE:	<ul style="list-style-type: none"> • -40C to 85C, convection cooled
STORAGE TEMPERATURE:	<ul style="list-style-type: none"> • -45C to 85C

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
1-9113-000	14 Ports Gigabit Ethernet Switch, Wide Range(6VDC-36VDC input range)
1-9113-001	14 Ports Gigabit Ethernet Switch, Wide Range with Cooling Plate
1-9113-002	14 Ports Gigabit Ethernet Switch, input power 3.3VDC ±3%
1-CP9113-000	Cooling Plate Kit for MT9113
1-9113EVB-000	MT9113 Evaluation Board
1-ICE9113-000	14 Ports Gigabit Ethernet Switch, Wide Range with Cooling block and Evaluation Board



MILTECH™ 9113

Managed Military Grade Embedded Ethernet Switch
12 x 10/100/1000TX Ports + 2 x Gigabit Fiber Ports

