

## STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4012 Series datasheet, detailing the specific features and parameters of this variant of the M4012 Series power supplies.

**SERIES: M4012**

**CONFIGURATION: M4012-101**

### *ELECTRICAL SPECIFICATIONS:*

Input	Outputs					
	PO1	PO2	PO3	+12_Aux	-12_Aux	3.3_Aux
18-48V <sub>DC</sub>	12V/15A	3.3V/5A	5V/12A	12V/1A	-12V/1A	3.3V/5A

### *SPECIAL FEATURES:*

- Supports Mil-STD-704F 50V Transients
- Max combined Power up to 235W
- Support up to 180W @ 50mSec Holdup



**Cham, Switzerland**  
[www.enercon-europe.com](http://www.enercon-europe.com)  
[enercon@enercon-europe.com](mailto:enercon@enercon-europe.com)  
 +41-41-740-4554

#### Global Headquarters

**Netanya, Israel**  
[www.enercon.co.il](http://www.enercon.co.il)  
[sales@enercon.co.il](mailto:sales@enercon.co.il)  
 +972-73-246 9200



**Gurgaon, India**  
[www.mpsindia.in](http://www.mpsindia.in)  
[sales@mpsindia.in](mailto:sales@mpsindia.in)  
 +91-124-651 0010