STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4162 Series datasheet, detailing the specific features and parameters of this variant of the M4162 Series power supplies.

SERIES: M4162
CONFIGURATION: M4162-101

ELECTRICAL SPECIFICATIONS:

Input	Holdup Output
Up to $100V_{DC}$	800W@50mSec, Up to $85V_{DC}$

SPECIAL FEATURES:

- Hold-up Unit.
- 40 Joules useable energy.
- Internal EMI Filter.
- 46.11 System Management
- Caps charged to 85V@0.5 Sec. $I_{charge\ (AVG)} \approx 18A$
- MTBF 239,210 Hours, calculated IAW, MIL-HDBK-217F Notice 2 at +85 ℃, GF

NON ITAR

AS9100D CERTIFIED ISO 9001

ENERCON TECHNOLOGIES LTD
Cham, Switzerland
www.enercon-europe.com
sales@enercon-europe.com
+41-41-740-4554

Global Headquarters

Netanya, Israel
www.enercon.co.il
sales@enercon.co.il
+972-73-246 9200

MULTISPHERE POWER SOLUTIONS PVT. LTD.
Gurgaon, India
www.mpsindia.in
sales@mpsindia.in
+91-124-651 0010