

## STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4268 Series datasheet, detailing the specific features and parameters of this variant of the M4268 Series power supplies.

**SERIES: M4268**

**CONFIGURATION: M4268-101**

### ***ELECTRICAL SPECIFICATIONS:***

Input	Outputs					
	VS1	VS2	VS3	+12_Aux	-12_Aux	3.3_Aux
22-48V <sub>DC</sub>	12V/65A		5V/18A	12V/1.3A	-12V/1.3A	3.3V/15A

### ***SPECIAL FEATURES:***

- Input Voltage 22V-48V, supports transients per Mil-STD -704F
- VS1 and VS2 shorted Internally
- Current share for VS1, VS2, VS3
- 46.11 compatible communication

*Note: Specifications are subject to change without prior notice by the manufacturer.*



**Cham, Switzerland**  
[www.enercon-europe.com](http://www.enercon-europe.com)  
[enercon@enercon-europe.com](mailto:enercon@enercon-europe.com)  
 +41-41-740-4554

#### **Global Headquarters**

**Netanya, Israel**  
[www.enercon.co.il](http://www.enercon.co.il)  
[sales@enercon.co.il](mailto:sales@enercon.co.il)  
 +972-73-246 9200



**Gurgaon, India**  
[www.mpsindia.in](http://www.mpsindia.in)  
[sales@mpsindia.in](mailto:sales@mpsindia.in)  
 +91-124-651 0010